

Filtration Chemical

INDION® 8212

RO/NF/EDR Antiscalant

Application

INDION 8212 is an excellent multifunctional antiscalant/antifoulant for use in reverse osmosis, nano filtration and electro dialysis reversal systems. It is highly effective in inhibiting the formation and growth of calcium carbonate, calcium sulphate, calcium fluorides and metal oxides scales.

It minimises or eliminates acid feed for scale control, also disperses metal ions and colloids thus improving system efficiency.

Foulant	Index	Saturation limit with INDION 8212
CaCO ₃	*LSI	+2.6
CaSO ₄	# IP _b /K _{sp}	3
CaF ₂	# IP _b /K _{sp}	120

*Langeliar saturation Index; #on product in brine/solubility product of salt

Benefits & Features

- Highly effective across a broad spectrum of waters
- Minimises scaling and reduces the frequency of membrane cleaning
- Will reduce and usually replace the need for acid addition
- Excellent threshold inhibitor and crystal distorter of alkaline earth metals & silica scales
- Effective at low dosages
- Compatible with most membrane types
- Maintains colloids and metal ions in suspension until rejection thus minimising fouling

Product Specifications

Appearance	:	Clear colourless to pale yellow liquid
pH as supplied	:	10.0 - 11.5
Specific gravity	:	1.30 - 1.40
Solubility in water	:	Miscible in all ratios
Flash point	:	Non-flammable aqueous solution

Direction for Use

INDION 8212 should be injected in membrane systems after chlorine and sodium meta-bisulphite treatment as such or diluted. Dilution should be done with RO permeate or equivalent quality water for preferably not less than 10% solution. The solution should be kept covered and should be consumed within 4-5 days. INDION 8212 is not compatible with residual cationic polymers from the pre-treatment.

A dosage projection is required for each system to determine the proper dosage. A complete water analysis and system details are required based on which accurate dosage projection can be recommended by our sales representative.

Limitations and Handling

INDION 8212 is not considered hazardous but as with all industrial chemicals, care should be taken in its handling and use. Keep the container closed when not in use, the product should not be swallowed and prolonged contact with the skin should be avoided. Wear goggles & face shield and rubber gloves while handling this product.

Storage, Packaging & Shelf Life

INDION 8212 is available in 25 kg pails, 50/200 kg drums and 1300 kg IBC. Shelf life of INDION 8212 is two years under normal handling and storage conditions. It is advisable to keep container tightly closed in a cool place.

The information contained herein, is to the best of our knowledge, true and accurate. No warranty, expressed or implied is made except that the products discussed herein complies with the chemical description. Ion Exchange (India) Ltd. shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product.

INDION is the registered trademark of Ion Exchange (India) Ltd.

ION EXCHANGE (INDIA) LTD.

Corporate Office

Ion House, Dr. E. Moses Road,
Mahalaxmi, Mumbai 400 011
Tel: +91 22 3989 0909
Fax: +91 22 2493 8737
E-mail: ieil@ionexchange.co.in

Chemical Division

4th Flr, Riviera Apartment, Dwarkapuri Colony,
Punjabgutta, Hyderabad 500 082
Tel: +91 40 3066 3101 / 02 / 03
Fax: +91 40 3066 3104
E-mail: hydcro@ionexchange.co.in

International Division

R-14, T.T.C MIDC, Thane - Belapur Road,
Rabale, Navi Mumbai 400 701
Tel: +91 22 3989 0909 / 3913 2400
Fax: +91 22 2769 7918
E-mail: export.sales@ionexchange.co.in

OFFICES

Regional	Telephone	Fax	E-mail
Chennai	+91 44 3989 0909 / 3910 2900	+91 44 2815 3361	checro@ionexchange.co.in
Delhi	+91 11 3989 0909 / 3054 3200	+91 11 2577 4837	delcro@ionexchange.co.in
Kolkata	+91 33 3989 0909 / 3043 3400	+91 33 2400 4345	calcro@ionexchange.co.in
Vashi	+91 22 3989 0909 / 3913 2300	+91 22 2788 9839	mumcro@ionexchange.co.in
Branch			
Bengaluru	+91 80 2204 2888	+91 80285 32002	bngcro@ionexchange.co.in
Bhubaneswar	+91 674 326 9525 / 257 1491		bbsr@ionexchange.co.in
Chandigarh	+91 172 274 5011	+91 172 274 4594	delcro@ionexchange.co.in
Hyderabad	+91 40 3066 3101 / 02 / 03	+91 40 3066 3104	hydcro@ionexchange.co.in
Lucknow	+91 522 319 9911	+91 11 2577 4837	lko.general@ionexchange.co.in
Vadodara	+91 265 302 7489 / 90	+91 265 2352 932	brdcro@ionexchange.co.in
Visakhapatnam	+91 891 324 6253		sales.vizag@ionexchange.co.in

Factories: Ankleshwar | Hosur | Patancheru | Rabale | Verna

All India Service and Dealer Network

www.ionindia.com